



Modulo is a magnetic, LED track system in extruded aluminium with a range of versatile fittings available. The track is available in 2m lengths and can be interconnected via a connecting plate to form a recessed, surface mounted or pendant system. The power supply is remote. Opal is a recessed Modulo fitting in die-cast aluminium with opal diffuser, available in three sizes and wattages












Dimensions	34mm x 640mm x 56mm
Finish	White (WH) / Black (BK)
Configurations	Track Mounted
Code / Description	75M2030 / Warm White 3000K 20W
Light Source	LED
Lumen Output	858lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Voltage	24 Vdc



Remote Driver Options

Remote Driver	Fixed Output / Phase-Cut / 1-10V / DALI

Additional Information



3 Circuits Modulo System - Surface / Pendant

Dimensions	39mm x 76mm x 1000-1500-2000mm	
Finish	White (WH) / Black (BK) / Custom Colour (CC)	
Configurations	Surface / Pendant	
Code	75SM	
Voltage	24 Vdc	











/		
Code / Description	75SUSKIT / Suspension Kit	
Finish	White / Black / Custom Colour	
Code / Description	75RECKIT / Recessed Kit	
Finish	White / Black / Custom Colour	
Code / Description	75DWN90CNR / "L" 90° Corner	
Finish	White / Black / Custom Colour	06 E. T. S.
Code / Description	75INR90CNR / Inner Corner	90 4
Finish	White / Black / Custom Colour	88
Code / Description	75OUT90CNR / Outer Corner	123 123 123
Finish	White / Black / Custom Colour	888
Code / Description	75MECHCONN / Connection Kit	0
Finish	Black / Custom Colour	Ů
Code / Description	75ELECCONN / Conductor	
Finish	Black / Custom Colour	
Code / Description	75COVER / Cover 3m	
Finish	White / Black / Custom Colour	
		~

Additional Information